



PCB LAYOUT
Ref.

- MATERIALS:
- BOTTOM HOUSING-DSM STANYL TE250F6 (NYLON-46)
HEAT DEFLECTION TEMP.290°
BLACK COLOR, UL94V-0
 - TOP HOUSING-PBT POLYESTER UL94V-0
MIXED GLASS FIBER, BLACK COLOR.
 - CONTACTS-0.35mm THICK PHOS-BRONZE PLATED
WITH HARD GOLD AND GOLD FLASH IN
SOLDER AREA.
 - SHIELD-0.25mm THICK COPPER ALLOY,
PLATED WITH NICKEL.
- CAVITY CONFIRMS TO FCC RULES AND REGULATIONS

REV.	ECN. NO.	DRAWN	DATE
A	NEW	JOHN	28/03/2015

DST-conn Tech. Co., Ltd. **HSF** Compliant

⊗:QUALITY CONTROL ITEM		GENERAL TOLERANCE		PART NO.: 24JS66D-xxxxx		
APPROVED		.X± 0.38	X.'± 2'	TITLE:RJ45 2X4 PORT 8P8C		
CHECKED		.XX± 0.25	.X'± 1'	W/ LED , SHELL , T/S		
DRAWN		.XXX± 0.13		UNIT: mm	SCALE: 1:1	SHEET: 1/1
						REV.: A

説明: △ :備註 ◇ :版本變更 ① :尺寸序號 ■ :重點尺寸 ▼ :CPK尺寸

F
E
D
C
B
A

F
E
D
C
B
A
SIZE: A4

1 2 3