

F

E

D

C

B

A

RoHS Compliant

SYMBOL

REV.

REVISION

APPROVAL

DATE

A

新版圖紙

Winky

2003. 01. 10

SPECIFICATIONS

CURRENT RATING: 2.0A @ 80 °C AMBIENT

OPERATING TEMP RANGE: -40 °C TO +125 °C

MAX PROCESSING TEMP: NT6T: 260 °C FOR 10 SECONDS

PBT: 200 °C FOR 20 SECONDS

INSULATOR MATERIAL: PBT OR PA6T BLACK

CONTACT MATERIAL: BRASS

PLATING: GOLD FLASH OR OTHER

PART NUMBER: DH12-M x 0 xx 0L20L

xx: NO.OF CONTACT

B: PA6T

G: PBT

2.00

 2.00 ± 0.05 $SQ0.50 \pm 0.02$

4.00

3.50

2.80

 2.00 ± 0.05

(Non-Accum)

 $\phi 0.80 \pm 0.05$ $B = (A - \text{Pitch}) \pm 0.20$ $A = (\text{Pitch} \times \text{No, of contact}) \begin{matrix} +0.1 \\ -0.5 \end{matrix}$

2.00

P.C.B LAYOUT

DST-conn Tech. Co., Ltd.

PART NAME		PH P2.0 90° DIP SERIES		DRAWING	Winky	DWG. No.	DH12
PART NO.		DH12-Mx0xx0L20L		CHECK	Roy	REV.	A
UNIT : mm	TOLERANCE UNLESS OTHERWISE SPECIFIED	X. X ±0.30	ANGLE ±2°	APPROVAL	John	DATE	2003. 01. 10
		X. XX ±0.20		SCALE	1:1	PAGE	1 OF 1
		X. XXX ±0.10					

COPYRIGHT RESERVED, PLEASE DO NOT COPY.

F

E

D

C

B

A