



RoHS Compliant

SYMBOL	REV.	REVISION	APPROVAL	DATE
	A	新版圖紙	Winky	2013. 07. 15

SPECIFICATIONS
CURRENT RATING:1.0A AC,DC
VOLTAGE RATING:250V AC,DC
OPERATING TEMP RANGE: -65°C TO +125°C
MAX PROCESSING TEMP:PA6T:260°C FOR 10SECONDS
PA9T:260°C FOR 10SECONDS PBT:230°C FOR 20SECONDS
INSULATOR MATERIAL: PA6T OR PA9T(HF) OR PBT
CONTACT MATERIAL:BRASS
PLATING:GOLD FLASH OR OTHER

pin /Row	A	B	C
6	5.08	15.24	12.94
8	7.62	17.78	15.48
10	10.16	20.32	18.02
14	15.24	25.40	23.10
16	17.78	27.94	25.64
20	22.86	33.02	30.72
24	27.94	38.10	35.80
26	30.48	40.64	38.34
30	35.56	45.72	43.42
34	40.64	50.80	48.50
40	48.26	58.42	56.12
44	53.34	63.50	61.20
50	60.96	71.12	68.82
60	73.66	83.82	81.52
64	78.74	88.90	86.60

PART NUMBER: DH19-B x 0 xx 0L54L- x

B:BLACK
E:BLUE
Y:YELLOW
W:WHITE

xx:Number of contact

B:PA6T C:PA9T(HF)
G:PBT

P.C.B LAYOUT

DST-conn Tech. Co., Ltd.

COPYRIGHT RESERVED, PLEASE DO NOT COPY.

PART NAME		BOX P2.54 180° DIP SERIES			DRAWING	Winky	DWG. No.	DH19
PART NO.		DH19-Bx0xx0L54L-x			CHECK	Roy	REV.	A
	UNIT :	TOLERANCE UNLESS	X. X ±0.30	ANGLE	APPROVAL	John	DATE	2013. 07. 15
	mm	OTHERWISE SPECIFIED	X. XX ±0.20 X. XXX ±0.10		SCALE	1:1	PAGE	1 OF 1