

F

E

D

C

B

A

RoHS Compliant

SYMBOL

REV.  
AREVISION  
新版圖紙APPROVAL  
WinkyDATE  
2003/08/20

Features:

- Available in 2 thru 24 circuits
- Material: Nylon 6T
- .0246"(0.625mm) square pin
- Standard color: Black
- UL file No.: E114003

Ordering Information

Part No.	Pin material
DP01-DBSxxGL30A	Tin-plated brass pin
DP01-DB0xxGL30A	Gold-flash brass pin

&amp;&amp; xx = 02 ~ 24

Specifications:

• Current rating:

Wire size	# 20	# 22	# 24	# 26	# 28	# 30
Ampere	5 A	5 A	4 A	3 A	2 A	1 A

- Voltage rating: 250V AC(RMS) or DC
- Contact resistance: 10mΩ Max.
- Dielectric strength: 1500V AC/minute

- Ambient temperature range: -40°C ~ 105°C  
(Including temperature rise)

Circuit No. 1

Dimensional Information

Circuits	Dim. A	Dim. B	Circuits	Dim. A	Dim. B	Circuits	Dim. A	Dim. B	Circuits	Dim. A	Dim. B	Circuits	Dim. A	Dim. B	Circuits	Dim. A	Dim. B
2		6.65	6	6.0	12.65	10	12.0	18.65	14	18.0	24.65	18	24.0	30.65	22	30.0	36.65
4	3.0	9.65	8	9.0	15.65	12	15.0	21.65	16	21.0	27.65	20	27.0	33.65	24	33.0	39.65

DST-conn Tech. Co., Ltd.

COPYRIGHT RESERVED, PLEASE DO NOT COPY.

PART NAME		3.00mm POWER CONN DUAL ROW 90D			DRAWING		Winky		DWG. No.		DP01	
PART NO.		DP01-DBxxxGL30A			CHECK		Roy		REV.		A	
UNIT : mm	TOLERANCE UNLESS OTHERWISE SPECIFIED		X. X X. XX X. XXX		ANGLE		APPROVAL		DATE		2003/08/20	
					±2°		SCALE		PAGE		1 OF 1	

F

E

D

C

B

A